



LIFE-CYCLE COST COMPARISON OF ALTERNATIVE SURFACING FOR STEEP SLOPES ON LOW-VOLUME ROADS IN GHANA

**8TH AFRICA TRANSPORTATION TECHNOLOGY
TRANSFER CONFERENCE – 2017**

**Joseph Anochie-Boateng
CSIR Built Environment, South Africa**

10 May 2017

ACKNOWLEDGEMENTS



AfCAP
Africa Community Access Partnership



DFID is the sponsor of the project

This study was carried out under the terms of a contract between Cardno Emerging Markets (UK) Ltd (the AfCAP/ReCAP Managers) and CSIR in partnership with BRR, as part of the DFID-funded AfCAP Research in Community Access Partnership (ReCAP) programme. The Project Team comprised Joseph Anochie-Boateng (Team Leader); Edmund Debrah (Local Civil Engineer). The valuable support and technical advice of Les Sampson and Paulina Agyekum is gratefully acknowledged. The Department of Feeder Roads (DFR) provided office space for the project team, relevant information on feeder roads in Ghana, and all land transport for site visits.

Co-authors of the paper – Les Sampson & Paulina Agyekum (Cardno UK Ltd), K Osafo Ampadu (DFR, Ghana)




ReCAP
Research for Community Access Partnership



SCOPE OF THE PROJECT

- Project is a two-phase study on alternative surfacing (*gravel wearing course*) for steep slopes on low-volume (feeder) roads in Ghana
 - ***Phase 1: involved a desk study, preliminary site evaluation and scoping for the phase 2 study (GHA2065A)***
 - ***CSIR/BRRI partnership (Jan 2016 – May 2016)***
 - ***Phase 2: involves design, construction and monitoring of selected pavement options identified in the phase 1 study (GHA2065B)***
 - ***CSIR/BRRI partnership (Feb 2017 – Feb 2020)***

MOTIVATION / NEED



THE SITUATION

- Erosion and drainage



THE SITUATION

- Erosion and drainage



CURRENT SOLUTIONS

- Appropriate?



CURRENT SOLUTIONS

- Appropriate?



MAIN OUTCOME OF PHASE 1



1. Bituminous surfacings

- lateritic gravel modified with sand / quarry dust + AC10 binder
- Otta seal (1x) lateritic gravel modified with sand/quarry dust + emulsion
- 2x surface dressing (seal)



2. Concrete surfacings

- concrete block paving (interlocking)
- ultra-thin reinforced concrete
- roller compacted concrete



3. Cobblestone/stone setts

- granite
- quartzite
- sandstone

Mechanical stabilisation (1. lateritic gravel + crushed stone/quarry dust; 2. lateritic gravel + sand/ pozzolana)

OBJECTIVE OF PAPER

- To present a life-cycle cost comparison of **six pavement options** proposed for steep slopes on feeder roads in Ghana
 1. **70 mm ultra-thin reinforced concrete** on mechanically stabilised laterite base [crushed stone and quarry dust]
 2. **50 mm thin hot mix asphalt** on mechanically stabilised laterite base
 3. **Interlocking concrete paving blocks** on mechanically stabilised laterite
 4. **Screened gravel single Otta seal** [14mm-25mm aggregates] on 100mm and 150mm mechanically stabilised base and subbase layers
 5. **Stone setts / cobbles** [100 mm-250 mm] arranged on spread sand/quarry dust blinding of average depth 25 mm on 100 mm stabilised laterite
 6. **Double seal** [10 mm and 19 mm] on 100 mm stabilised base and 150 mm stabilised sub-base

SURFACING OPTIONS



Ultra-thin reinforced concrete



Thin hot mix asphalt

SURFACING OPTIONS



Interlocking concrete paving blocks



Screened gravel single Otta seal

SURFACING OPTIONS



Stone setts / cobbles



Double seal

INITIAL CONSTRUCTION COSTS


Option #	Pavement structure	Provisional Sum GBP	Lined Side Drains Cost GBP	Pavement Layers Cost GBP	Culvert Cost GBP	Estimated Total Cost GBP	Cost Per Sq. Metre GBP
1	70 mm ultra-thin rein. concrete on 200 mm mechanically stabilised laterite base	12 450.00	28 636.00	53 340.00	6000.00	100 426.00	66.95
2	50 mm hot-mix asphalt with processed lateritic gravel and AC-10 bitumen on 200 mm mechanically stabilised base	12 450.00	28 636.00	89 100.00	6000.00	136 186.00	90.79
3	Interlocking concrete paving blocks on 150 mm stabilised laterite [crushed stone and quarry dust]	12 450.00	28 636.00	84 696.00	6000.00	131 782.00	87.85
4	Screened gravel single Otta seal [14mm-25mm aggregates] on 100mm mechanically stabilised base and 150mm mechanically stabilised subbase	12 450.00	28 636.00	55 200.00	6000.00	102 286.00	68.19
5	Stone setts / cobbles [100 mm-250 mm] arranged on spread sand/quarry dust blinding of average depth 25 mm on 100 mm stabilised laterite	12 450.00	28 636.00	74 646.00	6000.00	121 732.00	81.15
6	Double seal [10 mm and 14 mm] on 100 mm stabilised base and 150 mm stabilised sub-base	12 450.00	28 636.00	85 200.00	6000.00	132 286.00	88.19

LIFE-CYCLE COST ANALYSIS

Surfacing	Surfacing Life (Years)	Structural Maintenance		Initial Cost / m ² (GBP)	Maintenance Cost /m ² (GBP)	Life-Cycle Cost / m ² (GBP ¹)		
		Strategy	After x years			r = 8%	r = 10%	r = 12%
70 mm UTRC	30-50	Repairs	20	66.95	0.37	70.58	70.10	69.71
50 mm HMA	15-20	overlay	15	90.79	5.24	92.44	92.05	91.75
Paving Blocks	30-50	Repairs	10	87.85	4.40	94.03	92.26	91.11
Gravel Single Otta Seal	5-8	Reseal	3	68.19	4.20	71.05	70.79	70.57
Stone Setts / Cobbles	20-30	Repairs	20	81.15	9.44	81.38	81.31	81.26
Double Seal	10-15	Fog spray	3	88.19	0.52	89.27	89.12	89.00
		Fog spray	10		0.52			
		Reseal	12		1.05			

$$PWOC = C + M \downarrow 1 (1+r)^{\uparrow - x \downarrow 1} + \dots + M \downarrow j (1+r)^{\uparrow - x \downarrow j} - S(1+r)^{\uparrow - z}$$

LIFE-CYCLE COST ANALYSIS



CONCLUSIONS

- **Cost difference between the initial construction and the total life-cycle insignificant for all six pavement options selected for this study**
- **All six pavement options identified through this project are feasible for the current and future studies**
- **LCCA of gravel wearing course on the steep sections of the feeder roads in Ghana (**GBP 106.07 per square metre**) > the three relatively expensive options (i.e. double seal, paving blocks, thin HMA)**
- **Current policies of the DFR may influence the final decision on which particular pavement options to adopt for the steep gradients on feeder roads in Ghana**

RECOMMENDATIONS

- **Four pavement options proposed for Phase 2**
 - 1. 70 mm ultra-thin reinforced concrete on mechanically stabilised laterite base [crushed stone and quarry dust]*
 - 2. 50 mm thin hot mix asphalt on mechanically stabilised laterite base*
 - 3. Stone setts / cobbles [100 mm-250 mm] arranged on spread sand/quarry dust blinding of average depth 25 mm on 100 mm stabilised laterite*
 - 4. Interlocking concrete paving blocks on mechanically stabilised laterite*
- **Introduce mechanical stabilisation of lateritic soils as the common materials for the base/subbase layers of all pavement options on steep sections of feeder roads in Ghana**

ULTIMATELY...

To enable experience to be gained with a range of alternative surfacing that better utilise local resources in a sustainable way, minimising whole-life-costs and supporting the socio-economic activities of the community. The overall goal is to complement national standards with cost-effective surfacing options for steep gradient sections on feeder roads in Ghana.



Thank You

Joseph Anochie-Boateng (janochieboateng@csir.co.za)